

Application Serial No. 10/510,612

In the Claims:

1. (Currently Amended) A touch sensor comprising,  
a first coupling member constructed in a united manner with a pedestal,  
plate springs arranged to be parallel each other, one end sides of the plate  
springs being fixed to both ends of the first coupling member respectively,  
a second coupling member to couple other ends of the plate springs to each  
other,  
a magnet installed in a manner that the side of each plate spring corresponds  
to the side of either magnetic pole,  
a pipe mounted to each plate springs in parallel to the direction of the  
magnetic poles of the magnet, and  
a detecting means Hall IC located near the magnetic pole boundary line of  
the magnet for detecting a displacement of the magnet caused by an external force  
applied to the pipe,  
wherein the each plate has a rigid part with rigidity on the base end side,  
and an elastic part with elasticity on the both end sides.
2. (Original) A touch sensor as claimed in claim 1 characterized by comprising  
an elastic body to cancel the effect of gravity on the second coupling member.

Application Serial No. 10/510,612

3. (Currently Amended) A touch sensor as claimed in claim 1 or 2

characterized by comprising,

a supporting member having one end side fixed to the first coupling member and other end side provided with the ~~detecting means~~ Hall IC or the magnet, the supporting member inclined from the one end side to the other end side, and

an adjusting member for adjusting the distance between the supporting member and the pedestal,

wherein the magnet or the ~~detecting means~~ Hall IC is mounted to the second coupling member.

4. (Currently Amended) A touch sensor as claimed in ~~claims 1 to 3~~ claim 1 or 2 characterized in that holes are provided to portions where displacement is caused by an external force applied to the pipe.

5. (Currently Amended) A touch sensor as claimed in ~~claims 1 to 4~~ claim 1 or 2 characterized in that one end of the pipe is provided with a rigid anvil to receive an external force.

Application Serial No. 10/510,612

6. (Currently Amended) A touch sensor as claimed in ~~claims 1 to 5~~ claim 1 or 2 characterized by comprising a notifying member for notifying whether or not a signal is output from the ~~detecting means~~ Hall IC.
7. (Currently Amended) A touch sensor as claimed in ~~claims 1 to 6~~ claim 1 or 2 characterized in that pedestals are provided to at least two parts on a bottom surface of the pedestal.
8. (Currently Amended) A touch sensor as claimed in ~~claims 1 to 7~~ claim 1 or 2 characterized in that the pipe is provided with a regulating member for regulating a displacement of pipe body.
9. (Currently Amended) A touch sensor as claimed in ~~claims 1 to 7~~ claim 1 or 2 characterized in that the pipe is provided so that its other end regulates a displacement of the pipe body.